



WHITE

Luna+

White Safety shoes for food, medical and chemical industry

Overview



Feedback

For all those doing their jobs in industries imposing major hygiene constraints, the White Range has been designed with a one-piece upper, without assembly stitching. Made with a new thicker material called Dry-Tek®, this range offers enhanced resistance against chemical risks and helps to ensure optimum hygiene with its Cambrelle+ Amicor® antibacterial lining and “refreshing” treatment: the fibres are treated to eliminate bacteria and fungi, and to combat perspiration odours. This lining is made using a new process: a microencapsulated deodorant is released by rubbing to ensure lasting freshness.

Luna+

S2 HI CI FO SR

- Dry-Tek® material resistant to 12 chemical products upper
- Cambrelle+ Amicor® with “refreshing” treatment lining
- Padded synthetic PU material ankle protection
- Composite 200 Joules Light System® toe cap
- Antibacterial and antimicrobial foam insole
- PU 2D sole
- EN ISO 20345:2022 SRC

Specifications

- **Additional standards**
 - CI, HI, WRU, FO, A, E, SRC
- **Weight US (lbs per shoes)**
 - 0.88
- **Weight US (lbs per pair)**
 - 1.76
- **Weight EU (g per shoes)**
 - 400
- **Weight EU (g per pair)**
 - 800
- **Weight**
 - Light (<1000g)
- **Water resistance (WR)**
 - WRU
- **Upper material and finition**
 - Microfibre
- **Upper material**
 - Microfibre
- **USA size Men**
 - 4, 5, 5.5, 6, 7, 7.5, 8, 9, 10, 11, 11.5, 12, 13, 14, 15
- **USA Size Ladies**
 - 5, 6, 7, 7.5, 8.5, 9, 9.5, 10.5, 11.5
- **UK/AUST Men sizes**
 - 3, 4, 4.5, 5, 6, 6.5, 7, 8, 9, 10, 10.5, 11, 12, 13, 14
- **UK/AUST Ladies sizes**
 - 5, 6, 6.5, 7, 8, 8.5, 9, 10, 11
- **Toe-cap-mix**
 - 200 joules resistance in composite
- **Toe cap energy absorption**
 - 200j
- **Stronger slip resistance**
 - SRA, SRC
- **Slip resistance 2011**
 - SRC
- **Size range**
 - 35-49
- **Size**
 - 35, 36, 37, 38, 39, 40, 41, 42, 43, 44, 45, 46, 47, 48, 49
- **Security toe cap material**

- Composite
- **Risk foot display**
 - Impact, Water penetration resistant upper material, Slip (advanced), Cold, Antistatic
 - Impact, Water penetration resistant upper material, Slip (advanced), Cold, Antistatic
- **Risk family**
 - Impact, Liquid, Slip in liquid, Heat, Cold, Antistatic
- **Risk**
 - Impact, Tightness, Grip in liquid, Heat, Cold, ESD
- **Product kind**
 - Low shoes
- **Product Style**
 - 120201
- **Outsole material foot**
 - PU multi
 - PU multi
- **Outsole material**
 - PU, 2d
- **Oil resistance (FO)**
 - FO
- **Midsole material (pierce resistance)**
 - None
- **Metal free**
 - yes
- **Heel energy absorption (E)**
 - E
- **Heat insulation (HI marking) (HI)**
 - HI
- **Heat Insulation (HI)**
 - HI
- **Grip in liquid foot**
 - SRC / SR (ceramic and steel)
- **Footbed finition**
 - Foam
- **Footbed characteristic**
 - Antimicrobial
- **Fastening**
 - None
- **Electric properties (ESD / A / C)**
 - A
- **EN iso**
 - EN ISO 20345:2011

- **EN ISO 20345:2011 (toe-cap 200j)**
 - S2
- **Colors of the gloves**
 - White, Grey
- **Cold insulation (CI)**
 - CI
- **Category letter**
 - S
- **Category foot**
 - S2
- **Brand**
 - MTS
- **Benefits element**
 - Washable, Metal free, Shock absorbtion, Made in Europe



Please sign in to view part numbers available for purchase based on your account

[Sign In](#)

Search

Part Number	120201-35
Description	LUNA+ S2 SIGN IN
Part Number	120201-36
Description	LUNA+ S2 SIGN IN
Part Number	120201-37
Description	LUNA+ S2 SIGN IN
Part Number	120201-38
Description	LUNA+ S2 SIGN IN
Part Number	120201-39
Description	LUNA+ S2 SIGN IN
Part Number	120201-40
Description	LUNA+ S2 SIGN IN
Part Number	120201-41
Description	LUNA+ S2 SIGN IN
Part Number	120201-42

Feedback

Description	LUNA+ S2 SIGN IN
Part Number	120201-43
Description	LUNA+ S2 SIGN IN
Part Number	120201-44
Description	LUNA+ S2 SIGN IN



Please sign in to view part numbers available for purchase based on your account

Sign In

Honeywell
Industrial Automation
855 S Mint St
Charlotte, NC 28202
800-582-4263

Product name
© Current year Honeywell International Inc.
All rights reserved.

